

ARCOAGRO ON-LAND 180



ARCOAGRO 180 - SPRING 2in1







STANDARD EQUIPMENT

- Mouldboard model: KV09, LM35, LM40
- Trashboard
- Extension wing LM35, LM40
- Fork hinge cat. 3
- Working width per body: 35, 41, 47 cm
- **Protection by shear bolt**
- Interbody distance: 1000 mm
- Under beam clearance: 800 - 820 mm
- Vacuum hydraulic accumulator
- Wheel FLOTATION 500/45-22,5

ABOVE-STANDARD EQUIPMENT

- Mouldboard KV28
- Slatted boards PS40
- Extension wing KV09
- Skimmer type K2
- Rolling coulter Ø 480
- Sword landsides
- Knife coulter
- Additional plough body ArcoAgro On-Land
- Front supporting wheels
- Bushings for tractors K744
- Lightning

TECHNICAL SPECIFICATIONS

Number of furrows		5+	5+1	6+	7 (6+1)	8 (6+1+1)	9 (7+1+1)
	kg	2 977	3 220	3 463	3 733	4 000	
	hp	180 - 250		230 - 300	240 - 400	270 - 500	
	mm	180x180x10 					

Plough weights without accessory. Photos have only illustrative character.





STANDARD EQUIPMENT

- Mouldboard model: KV09, LM35, LM40
- Fork hinge cat. 3
- Trashboard
- Extension wing LM35, LM40
- Working width per body: 35, 41, 47 cm
- **Protection by non-stop leaf spring**
- Interbody distance: 1000 mm
- Under beam clearance: 750 - 770 mm
- Vacuum hydraulic accumulator
- Wheel FLOTATION 500/45-22,5
- Hydraulic front furrow adjustment+system On-land

ABOVE-STANDARD EQUIPMENT

- Mouldboard KV28
- Slatted boards PS40
- Extension wing KV09
- Skimmer Spring type S
- Skimmer Spring type K
- Rolling coulter Spring Ø 480
- Sword landsides
- Knife coulter
- Additional plough body ArcoAgro On-Land - Spring
- Front supporting wheels
- Bushings for tractors K744

TECHNICAL SPECIFICATIONS

Number of furrows		4+1	5+	5+1	6+	7 (6+1)	8 (6+1+1)	9 (7+1+1)
	kg	3 567		3 928	4 289	4 677	5 069	
	hp	145 - 200		175 - 300	250 - 300	240 - 400	290 - 500	
	mm	180x180x10 						

Plough weights without accessory. Photos have only illustrative character.