

ARCOAGRO 180



- STANDARD EQUIPMENT**

 - Mouldboard model: KV09, LM35, LM40
 - Trashboard
 - Extension wing LM35, LM40
 - Fork hinge cat. 3
 - Working width per body: 35, 41, 47 cm
 - **Protection by shear bolt**
 - Hydraulic front furrow adjustment
 - Interbody distance: 1000 mm
 - Under beam clearance: 800 - 820 mm
 - Vacuum hydraulic accumulator
 - Wheel FLOTATION 500/45-22,5

ABOVE-STANDARD EQUIPMENT

 - Mouldboard KV28
 - Slatted boards PS40
 - Extension wing KV09
 - Skimmer type K
 - Rolling coulter Ø 480
 - Sword landsides
 - Knife coulter
 - Additional plough body ArcoAgro 180
 - Bushings for tractors K744
 - Lightning

TECHNICAL SPECIFICATIONS

Number of furrows		4+1	5+	5+1	6+	7 (6+1)	8 (6+1+1)	9 (7+1+1)
	kg	2 950	2 950	3 170	3 170	3 431	3 676	3 953
	hp	145 - 200		175 - 300		250 - 300	200 - 400	240 - 500
	mm	180x180x10						

Plough weights without accessory. Photos have only illustrative character.