

ARCOAGRO 180 - SPRING 2in1



STANDARD EQUIPMENT

- Mouldboard model: KV09, LM35, LM40
- Fork hinge cat. 3
- Trashboard
- Extension wing LM35, LM40
- Working width per body: 35, 41, 47 cm
- **Protection by non-stop leaf spring**
- Interbody distance: 1000 mm
- Under beam clearance: 750 - 770 mm
- Vacuum hydraulic accumulator
- Wheel FLOTATION 500/45-22,5
- Hydraulic front furrow adjustment+system On-land



ABOVE-STANDARD EQUIPMENT

- Mouldboard KV28
- Slatted boards PS40
- Extension wing KV09
- Skimmer Spring type S
- Skimmer Spring type K
- Rolling coulter Spring Ø 480
- Sword landsides
- Knife coulter
- Additional plough body ArcoAgro On-Land - Spring
- Front supporting wheels
- Telescopic hydraulic cylinder
- Bushings for tractors K744



TECHNICAL SPECIFICATIONS

Number of furrows		4+1	5+	5+1	6+	7 (6+1)	8 (6+1+1)	9 (7+1+1)
	kg		3 567		3 928	4 289	4 677	5 069
	hp		145 - 200		175 - 300	250 - 300	240 - 400	290 - 500
	mm				180x180x10			

Plough weights without accessory. Photos have only illustrative character.