

DOWNHIL - SPRING



STANDARD EQUIPMENT

- Mouldboard model: KV09, LM35, LM40
- Trashboard
- Extension wing LM35, LM40
- Hydraulic cylinder with automated unit for turning
- Front furrow adjustment
- Support wheel AW 702 (Ø 710x265)
- Working width per body: 34, 39, 45 cm
- **Protection by non-stop leaf spring**
- Interbody distance: 950 mm
- Under beam clearance: 750 - 770 mm
- Fork hinge (2+, 3+, 3+1) cat. 2
- Fork hinge (4+, 4+1) cat. 3



ABOVE-STANDARD EQUIPMENT

- Mouldboard KV28
- Slatted boards PS40
- Extension wing KV09
- Skimmer Spring type S
- Skimmer Spring type K
- Rolling coulter Spring Ø 480
- Sword landsides
- Knife coulter
- Additional plough body Downhil - Spring
- Frame 140x140x10 mm 2+, 3+, 3+1
- Distance between bodies 1000 mm
- Memory cylinder
- Transport wheel
- Lightning



TECHNICAL SPECIFICATIONS

Number of furrows		2+	3+	3+1	4+	4+1
	kg	1 150	1 360	1 560	1 563	1 760
	hp	70 - 80		90 - 150	130 - 250	
	mm	120x120x10			140x140x10	

Plough weights without accessory. Photos have only illustrative character.