

# ARCOAGRO 180 - SPRING



## STANDARD EQUIPMENT

- Mouldboard model: KV09, LM35, LM40
- Trashboard
- Extension wing LM35, LM40
- Fork hinge cat. 3
- Working width per body: 35, 41, 47 cm
- **Protection by non-stop leaf spring**
- Hydraulic front furrow adjustment
- Interbody distance: 1000 mm
- Under beam clearance: 750 - 770 mm
- Vacuum hydraulic accumulator
- Wheel FLOTATION 500/45-22,5



## ABOVE-STANDARD EQUIPMENT

- Mouldboard KV28
- Slatted boards PS40
- Extension wing KV09
- Skimmer Spring type K
- Rolling coulter Spring Ø 480
- Sword landsides
- Additional plough body ArcoAgro - Spring
- Bushings for tractors K744
- Lightning



## TECHNICAL SPECIFICATIONS

| Number of furrows |    | 4+1 | 5+        | 5+1 | 6+         | 7 (6+1)   | 8 (6+1+1) | 9 (7+1+1) |
|-------------------|----|-----|-----------|-----|------------|-----------|-----------|-----------|
|                   | kg |     | 3 540     |     | 3 830      | 4 183     | 4 630     | 4 946     |
|                   | hp |     | 145 - 200 |     | 175 - 300  | 250 - 300 | 240 - 400 | 290 - 500 |
|                   | mm |     |           |     | 180x180x10 |           |           |           |

Plough weights without accessory. Photos have only illustrative character.